## NSN 5920-01-258-5033

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-258-5033
Body Style:
Axial terminal type
Terminal Material:
Copper or copper alloy
Terminal Surface Treatment:
Copper alloy
Overall Length:
11.625 inches
Mounting Slot Width:
0.406 inches
Body Length:
Between 7.125 inches and 7.813 inches
Overall Diameter:
2.910 inches
Case Material:
Fiber or ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
400.000
Terminal Width:
1.625 inches
Terminal Thickness:
0.250 inches
Maximum Voltage Rating In Volts:
600.0 ac
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/66 government specification
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5920-01-258-5033

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700