## NSN 5920-01-259-3087

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-259-3087 **Body Style:** Axial terminal type **Terminal Material:** Copper or copper alloy **Overall Length:** 7.120 inches **Mounting Slot Width:** 0.281 inches **Body Length:** 4.281 inches **Overall Diameter:** 1.690 inches **Case Material:** Fiber or ceramic or plastic, melamine, glass filled **Continuous Current Rating In Amps:** 125.000 **Terminal Width:** 1.125 inches **Terminal Thickness:** 0.183 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 500 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 200000.0 **Test Data Document:** 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81348-w-f-1814/59 government specification Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## **NSN 5920-01-259-3087** Cartridge Fuse - Page 2 of 2



Fiig:

A01700