NSN 5920-01-265-7676Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-265-7676
Body Style:
Hole type
Terminal Material:
Brass or copper
Overall Length:
Between 10.660 inches and 10.840 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 9.250 inches and 9.510 inches
Mounting Hole Diameter:
0.620 inches
Mounting Slot Width:
0.620 inches
Overall Diameter:
3.030 inches
Case Material:
Ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
1600.000
Terminal Width:
Between 2.320 inches and 2.440 inches
Center To Center Distance Between Inside Mounting Facilities Parallel To Length:
Between 5.750 inches and 6.750 inches
Terminal Thickness:
Between 0.410 inches and 0.470 inches
Maximum Voltage Rating In Volts:
600.0 ac
Circuit Over-current Interruption Type:
Normal instantaneous
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/49 government specification
Shelf Life:
N/a
Unit Of Measure:

NSN 5920-01-265-7676

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700