NSN 5920-01-265-7679

Cartridge Fuse - Page 1 of 1

A01700



View Online at https://aerobasegroup.com/nsn/5920-01-265-7679

| Body Style: |
|---|
| Hole type |
| Terminal Material: |
| Brass or copper |
| Overall Length: |
| Between 5.660 inches and 5.840 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 4.320 inches and 4.440 inches |
| Mounting Slot Width: |
| Between 0.246 inches and 0.316 inches |
| Overall Diameter: |
| 1.620 inches |
| Case Material: |
| Ceramic or plastic, melamine, glass filled |
| Continuous Current Rating In Amps: |
| 200.000 |
| Terminal Width: |
| Between 1.090 inches and 1.160 inches |
| Terminal Thickness: |
| Between 0.185 inches and 0.191 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac |
| Circuit Over-current Interruption Type: |
| Normal instantaneous |
| Interruption Indicator Method: |
| Opaque body |
| Features Provided: |
| Nonrenewable fusible element |
| Short-circuit/interrupt Current Rating In Amps: |
| 200000.0 |
| Test Data Document: |
| 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81348-w-f-1814/8 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |