## NSN 5920-01-276-2282



Cartridge Fuse - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5920-01-276-2282 **Body Style:** Axial terminal type **Terminal Surface Treatment:** Solder dip **Overall Length:** Between 9.620 inches and 9.630 inches **Mounting Slot Width:** 0.281 inches **Body Length:** Between 6.125 inches and 6.781 inches **Overall Diameter:** 2.120 inches **Continuous Current Rating In Amps:** 110.000 **Terminal Width:** 1.125 inches **Terminal Thickness:** 0.188 inches **Maximum Voltage Rating In Volts:** 600.0 ac **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Visible element **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 500 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 200000.0 **Test Data Document:** 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81348-w-f-1814/65 government specification Shelf Life: N/a **Unit Of Measure:** 

**Fiig:** A01700

No

**Demilitarization:**