NSN 5920-01-284-7305

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-284-7305

Body Style:

Rejection groove type

Terminal Material:

Brass or copper or copper alloy

Terminal Surface Treatment:

Solder dip

Overall Length:

Between 1.970 inches and 2.030 inches

Overall Diameter:

Between 0.554 inches and 0.570 inches

Case Material:

Ceramic or fiber or plastic, melamine, glass filled

Continuous Current Rating In Amps:

2.500

Fragility Factor:

Moderately rugged

Maximum Voltage Rating In Volts:

250.0 ac

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

10.0 500 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

200000.0

Test Data Document:

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-f-1814/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01700