

View Online at <https://aerobasegroup.com/nsn/5920-01-284-7306>

Body Style:

Axial terminal type

Terminal Material:

Copper or copper alloy

Terminal Surface Treatment:

Solder dip

Overall Length:

Between 5.820 inches and 5.940 inches

Mounting Slot Width:

Between 0.276 inches and 0.306 inches

Body Length:

Between 3.375 inches and 3.781 inches

Overall Diameter:

1.310 inches

Case Material:

Ceramic or fiber or plastic, melamine, glass filled

Continuous Current Rating In Amps:

90.000

Fragility Factor:

Moderately rugged

Terminal Width:

Between 0.715 inches and 0.785 inches

Terminal Thickness:

Between 0.122 inches and 0.128 inches

Maximum Voltage Rating In Volts:

250.0 ac

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

10.0 500 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

200000.0

Test Data Document:

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-f-1814/58 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01700