

View Online at <https://aerobasegroup.com/nsn/5920-01-290-3770>

**Body Style:**

Bushing mounted type

**Overall Length:**

2.470 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

1.260 inches

**Panel Thickness:**

0.060 inches

**Environmental Protection:**

Watertight

**Mounting Hole Style:**

Bushing mounting

**Lens Color:**

Amber

**Contact Material:**

Copper

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

330.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+23.0/+33.0

**Length From Front Protrusion To Mounting Surface:**

0.940 inches

**Bushing Thread Length:**

0.500 inches

**Cap Diameter:**

1.000 inches

**Bushing Hole Diameter:**

Between 0.877 inches and 0.882 inches

**Flatted Side Bushing Hole Length:**

Between 0.816 inches and 0.826 inches

**Screw Thread Diameter:**

0.138 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Special Features:**

Modified cap assembly for use on 28vdc

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 threaded stud and 1 screw

**Specification Data:**

81349-mil-f-19207/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0