

View Online at <https://aerobasegroup.com/nsn/5920-01-291-4946>

Body Style:

Tube type

Terminal Material:

Copper alloy

Terminal Surface Treatment:

Nickel plated

Overall Length:

1.500 inches

Overall Diameter:

0.406 inches

Case Material:

Fiber

Continuous Current Rating In Amps:

3.500

Fragility Factor:

Moderately rugged

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Circuit Over-current Interruption Type:

Normal instantaneous

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

12.0 200 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

10000.0

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15160/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01700