

View Online at <https://aerobasegroup.com/nsn/5920-01-300-0425>

**Body Style:**

Hole type

**Terminal Material:**

Brass or copper or copper alloy

**Overall Length:**

Between 7.030 inches and 7.210 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 5.190 inches and 5.310 inches

**Mounting Slot Width:**

Between 0.401 inches and 0.411 inches

**Overall Diameter:**

2.120 inches

**Case Material:**

Ceramic or fiber

**Continuous Current Rating In Amps:**

225.000

**Terminal Width:**

Between 1.590 inches and 1.660 inches

**Terminal Thickness:**

Between 0.247 inches and 0.253 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 600.0 dc

**Circuit Over-current Interruption Type:**

Time delay

**Interruption Indicator Method:**

Opaque body

**Features Provided:**

Nonrenewable fusible element

**Circuit Over-current Interruption Delay Time In Seconds:**

600.0 200 pct of current rating

**Short-circuit/interrupt Current Rating In Amps:**

200000.0

**Test Data Document:**

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-f-1814/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01700