## NSN 5920-01-300-0425

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-300-0425

| View Online at https://aerobasegroup.com/nsn/5920-01-300-0425                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Body Style:                                                                                                                                      |
| Hole type                                                                                                                                        |
| Terminal Material:                                                                                                                               |
| Brass or copper or copper alloy                                                                                                                  |
| Overall Length:                                                                                                                                  |
| Between 7.030 inches and 7.210 inches                                                                                                            |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                                                                        |
| Between 5.190 inches and 5.310 inches                                                                                                            |
| Mounting Slot Width:                                                                                                                             |
| Between 0.401 inches and 0.411 inches                                                                                                            |
| Overall Diameter:                                                                                                                                |
| 2.120 inches                                                                                                                                     |
| Case Material:                                                                                                                                   |
| Ceramic or fiber                                                                                                                                 |
| Continuous Current Rating In Amps:                                                                                                               |
| 225.000                                                                                                                                          |
| Terminal Width:                                                                                                                                  |
| Between 1.590 inches and 1.660 inches                                                                                                            |
| Terminal Thickness:                                                                                                                              |
| Between 0.247 inches and 0.253 inches                                                                                                            |
| Maximum Voltage Rating In Volts:                                                                                                                 |
| 600.0 ac and 600.0 dc                                                                                                                            |
| Circuit Over-current Interruption Type:                                                                                                          |
| Time delay                                                                                                                                       |
| Interruption Indicator Method:                                                                                                                   |
| Opaque body                                                                                                                                      |
| Features Provided:                                                                                                                               |
| Nonrenewable fusible element                                                                                                                     |
| Circuit Over-current Interruption Delay Time In Seconds:                                                                                         |
| 600.0 200 pct of current rating                                                                                                                  |
| Short-circuit/interrupt Current Rating In Amps:                                                                                                  |
| 200000.0                                                                                                                                         |
| Test Data Document:                                                                                                                              |
| 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental        |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                                              |
| Specification Data:                                                                                                                              |
| 81348-w-f-1814/9 government specification                                                                                                        |
| Shelf Life:                                                                                                                                      |
| N/a                                                                                                                                              |
| Unit Of Measure:                                                                                                                                 |
|                                                                                                                                                  |
| Demilitarization:                                                                                                                                |

No

## **NSN 5920-01-300-0425**Cartridge Fuse - Page 2 of 2



Fiig:

A01700