## NSN 5920-01-310-9279

Cartridge Fuse - Page 1 of 1

**Fiig:** A01700



View Online at https://aerobasegroup.com/nsn/5920-01-310-9279

Terminal Material:
Brass or copper or copper alloy
Overall Length:
Between 10.640 inches and 10.740 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
9.510 inches
Overall Diameter:
5.780 inches
Case Material:
Ceramic or fiberglass
Continuous Current Rating In Amps:
4000.000
Fragility Factor:
Moderately rugged
Terminal Width:
Between 4.690 inches and 4.810 inches
Center To Center Distance Between Inside Mounting Facilities Parallel To Length:
6.750 inches
Terminal Thickness:
Between 0.720 inches and 0.780 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Circuit Over-current Interruption Type:
Normal instantaneous
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/53 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No