NSN 5920-01-323-5778

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-323-5778

Body Style:

Hole type

Terminal Material:

Brass or copper alloy or copper

Overall Length:

Between 7.030 inches and 7.210 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 5.190 inches and 5.310 inches

Mounting Slot Width:

Between 0.401 inches and 0.411 inches

Overall Diameter:

2.120 inches

Case Material:

Ceramic

Continuous Current Rating In Amps:

400.000

Terminal Width:

Between 1.590 inches and 1.660 inches

Terminal Thickness:

Between 0.247 inches and 0.253 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

600.0 200 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

200000.0

Test Data Document:

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-f-1814/9 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5920-01-323-5778 Cartridge Fuse - Page 2 of 2

Fiig: A01700

