NSN 5920-01-323-6738

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-323-6738
Body Style:
Hole type
Terminal Material:
Brass or copper alloy or copper
Overall Length:
Between 7.030 inches and 7.210 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 5.190 inches and 5.310 inches
Mounting Slot Width:
Between 0.401 inches and 0.411 inches
Overall Diameter:
2.120 inches
Case Material:
Ceramic
Continuous Current Rating In Amps:
250.000
Terminal Width:
Between 1.590 inches and 1.660 inches
Terminal Thickness:
Between 0.247 inches and 0.253 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
600.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5920-01-323-6738Cartridge Fuse - Page 2 of 2



Fiig:

A01700