

View Online at <https://aerobasegroup.com/nsn/5920-01-331-8620>

**Body Style:**

Tube type

**Terminal Material:**

Brass or copper or copper alloy

**Terminal Surface Treatment:**

Nickel plated

**Overall Length:**

Between 1.469 inches and 1.531 inches

**Overall Diameter:**

Between 0.402 inches and 0.410 inches

**Case Material:**

Fiber

**Continuous Current Rating In Amps:**

12.000

**Fragility Factor:**

Moderately delicate

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**Circuit Over-current Interruption Type:**

Time delay

**Interruption Indicator Method:**

Opaque body

**Features Provided:**

Nonrenewable fusible element

**Circuit Over-current Interruption Delay Time In Seconds:**

12.0 200 pct of current rating

**Short-circuit/interrupt Current Rating In Amps:**

10000.0

**Test Data Document:**

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-15160/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01700