## NSN 5920-01-332-5625

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-332-5625

Body Style:
Rejection groove type
Terminal Material:
Brass or copper or copper alloy
Overall Length:
Between 1.970 inches and 2.030 inches
Overall Diameter:
Between 0.554 inches and 0.570 inches
Case Material:
Fiber or ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
3.200
Fragility Factor:
Moderately delicate
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/56 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A01700