NSN 5920-01-332-5626



Cartridge Fuse - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5920-01-332-5626 **Body Style:** Rejection groove type **Terminal Material:** Brass or copper or copper alloy **Overall Length:** Between 1.970 inches and 2.030 inches **Overall Diameter:** Between 0.554 inches and 0.570 inches **Case Material:** Fiber or ceramic or plastic, melamine, glass filled **Continuous Current Rating In Amps:** 1.800 **Fragility Factor:** Moderately delicate **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 500 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 200000.0 **Test Data Document:** 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81348-w-f-1814/56 government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A01700