

View Online at <https://aerobasegroup.com/nsn/5920-01-332-7992>

**Body Style:**

Axial terminal type

**Terminal Material:**

Copper or copper alloy

**Overall Length:**

Between 5.820 inches and 5.940 inches

**Mounting Slot Width:**

Between 0.276 inches and 0.306 inches

**Body Length:**

Between 3.375 inches and 3.781 inches

**Overall Diameter:**

1.310 inches

**Case Material:**

Fiber or ceramic or plastic, melamine, glass filled

**Continuous Current Rating In Amps:**

70.000

**Fragility Factor:**

Moderately rugged

**Terminal Width:**

Between 0.715 inches and 0.785 inches

**Terminal Thickness:**

Between 0.122 inches and 0.128 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Circuit Over-current Interruption Type:**

Time delay

**Interruption Indicator Method:**

Opaque body

**Features Provided:**

Nonrenewable fusible element

**Circuit Over-current Interruption Delay Time In Seconds:**

10.0 500 pct of current rating

**Short-circuit/interrupt Current Rating In Amps:**

200000.0

**Test Data Document:**

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-f-1814/58 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01700