## NSN 5920-01-332-7992

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-332-7992

Body Style:
Axial terminal type
Terminal Material:
Copper or copper alloy
Overall Length:
Between 5.820 inches and 5.940 inches
Mounting Slot Width:
Between 0.276 inches and 0.306 inches
Body Length:
Between 3.375 inches and 3.781 inches
Overall Diameter:
1.310 inches
Case Material:
Fiber or ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
70.000
Fragility Factor:
Moderately rugged
Terminal Width:
Between 0.715 inches and 0.785 inches
Terminal Thickness:
Between 0.122 inches and 0.128 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/58 government specification
Shelf Life:
N/a

-

**Unit Of Measure:** 

## NSN 5920-01-332-7992

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700