NSN 5920-01-367-9281

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-367-9281

| Body Style:Tube typeOverall Length:5.000 inchesOverall Diameter:0.750 inchesContinuous Current Rating In Amps:2.800Maximum Voltage Rating In Volts:600.0 acCircuit Over-current Interruption Type:Time delayInterruption Indicator Method:Hole blown in labelFeatures Provided:Nonrenewable fusible elementCircuit Over-current Interruption Delay Time In Seconds:10.0 200 pct of current ratingShort-circuit/interrupt Current Rating In Amps:3000.0Shelf Life:N/aUnit Of Measure:Demilitarization:No | |
|---|--|
| Overall Length: 5.000 inches Overall Diameter: 0.750 inches Continuous Current Rating In Amps: 2.800 Maximum Voltage Rating In Volts: 600.0 ac Gircuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: - | Body Style: |
| 5.000 inches Overall Diameter: 0.750 inches Continuous Current Rating In Amps: 2.800 Maximum Voltage Rating In Volts: 6.00.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: - | Tube type |
| Overall Diameter: 0.750 inches Continuous Current Rating In Amps: 2.800 Maximum Voltage Rating In Volts: 600.0 ac Gircuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: | Overall Length: |
| 0.750 inches Continuous Current Rating In Amps: 2.800 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: | 5.000 inches |
| Continuous Current Rating In Amps: 2.800 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: | Overall Diameter: |
| 2.800 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | 0.750 inches |
| Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Lift Of Measure: | Continuous Current Rating In Amps: |
| 600.0 ac Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: | 2.800 |
| Circuit Over-current Interruption Type: Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: | Maximum Voltage Rating In Volts: |
| Time delay Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | 600.0 ac |
| Interruption Indicator Method: Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Circuit Over-current Interruption Type: |
| Hole blown in label Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Time delay |
| Features Provided: Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Interruption Indicator Method: |
| Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Hole blown in label |
| Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Features Provided: |
| 10.0 200 pct of current rating Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Nonrenewable fusible element |
| Short-circuit/interrupt Current Rating In Amps: 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | Circuit Over-current Interruption Delay Time In Seconds: |
| 3000.0 Shelf Life: N/a Unit Of Measure: Demilitarization: | 10.0 200 pct of current rating |
| Shelf Life: N/a Unit Of Measure: Demilitarization: | Short-circuit/interrupt Current Rating In Amps: |
| N/a Unit Of Measure: Demilitarization: | 3000.0 |
| Unit Of Measure: Demilitarization: | Shelf Life: |
| Demilitarization: | N/a |
| | Unit Of Measure: |
| | |
| No | Demilitarization: |
| | No |
| Fiig: | Fiig: |

A01700