NSN 5920-01-478-4067

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-478-4067 **Body Style:** Panel mounted type **Overall Length:** 2.190 inches **Overall Height:** 2.280 inches **Overall Width:** 2.060 inches **Mounting Hole Diameter:** 0.152 inches **Mounting Hole Quantity: Panel Thickness:** 0.187 inches **Environmental Protection:** Watertight **Mounting Hole Style:** Panel mounting w/2 or 3 holes **Lens Color:** Amber **Contact Material:** Any acceptable **End Application:** Submarine atmosphere control and compressed air/gas **Fuse Accommodation Quantity:** 2 **Accommodated Fuse Length:** 1.500 inches **Accommodated Ferrule Diameter:** 0.406 inches **Resistor Rating:** 33.000 ohms **Indicating Lamp Voltage Range In Volts:** +90.0/+500.0 **Length From Front Protrusion To Mounting Surface:** 1.190 inches Cap Diameter: 0.620 inches **Mounting Hole Height:** 1.840 inches

Mounting Hole Width: 1.560 inches

NSN 5920-01-478-4067

Extractor Post Fuseholder - Page 2 of 2



Center To Center Distance Between Outside Mounting Holes Along Length:
1.940 inches
Center To Center Distance Between Outside Mounting Holes Along Width:
1.000 inches
Screw Thread Diameter:
0.164 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
33.0
Test Data Document:
31349-mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 threaded stud
Specification Data:
31349-mil-prf-19207/23 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No
Fiig:
A014a0
Mil-std (military Standard):
Mil-prf-19207 spec.