

View Online at <https://aerobasegroup.com/nsn/5920-01-483-2299>

Body Style:

Panel mounted type

Overall Length:

2.190 inches

Overall Height:

2.280 inches

Overall Width:

2.060 inches

Mounting Hole Diameter:

0.152 inches

Mounting Hole Quantity:

2

Panel Thickness:

0.187 inches

Environmental Protection:

Watertight

Mounting Hole Style:

Panel mounting w/2 or 3 holes

Lens Color:

Clear

Contact Material:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Resistor Rating:

330.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0

Length From Front Protrusion To Mounting Surface:

1.190 inches

Cap Diameter:

0.620 inches

Mounting Hole Height:

1.840 inches

Mounting Hole Width:

1.560 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.940 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

1.000 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Precious Material:

Silver

Test Data Document:

81349mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Specification Data:

81349-mil-prf-19207/23 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0

Mil-std (military Standard):

Mil-prf-19207 spec.