

View Online at <https://aerobasegroup.com/nsn/5920-01-498-4399>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Bushing mounted type

Overall Length:

Between 1.670 inches and 1.710 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 1.321 inches and 1.346 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Watertight and body sealed

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Length From Front Protrusion To Mounting Surface:

Between 0.540 inches and 0.580 inches

Bushing Thread Length:

0.360 inches

Cap Diameter:

Between 0.860 inches and 0.900 inches

Bushing Hole Diameter:

Between 0.877 inches and 0.887 inches

Flatted Side Bushing Hole Length:

Between 0.815 inches and 0.820 inches

Screw Thread Diameter:

0.190 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Test Data Document:

81349-mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 threaded stud and 1 screw

Specification Data:

81349-mil-prf-19207/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0

Mil-std (military Standard):

Mil-prf-19207 spec.