

View Online at <https://aerobasegroup.com/nsn/5920-01-498-4399>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Bushing mounted type

**Overall Length:**

Between 1.670 inches and 1.710 inches

**Bushing Diameter:**

0.625 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

Between 1.321 inches and 1.346 inches

**Panel Thickness:**

0.125 inches

**Environmental Protection:**

Watertight and body sealed

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.500 inches

**Accommodated Ferrule Diameter:**

0.406 inches

**Length From Front Protrusion To Mounting Surface:**

Between 0.540 inches and 0.580 inches

**Bushing Thread Length:**

0.360 inches

**Cap Diameter:**

Between 0.860 inches and 0.900 inches

**Bushing Hole Diameter:**

Between 0.877 inches and 0.887 inches

**Flatted Side Bushing Hole Length:**

Between 0.815 inches and 0.820 inches

**Screw Thread Diameter:**

0.190 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

500.0

**Test Data Document:**

81349-mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 threaded stud and 1 screw

**Specification Data:**

81349-mil-prf-19207/25 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0

**Mil-std (military Standard):**

Mil-prf-19207 spec.