

View Online at <https://aerobasegroup.com/nsn/5920-01-506-7720>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Rear panel mounted type

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

1.200 inches

Overall Width:

1.070 inches

Keyway Width:

0.105 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Incandescent lamp

End Application:

Panel, gear, ahead ay99 201-7429276

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

2050.0 ohms

Indicating Lamp Voltage Range In Volts:

+81.0/+90.0

Length From Front Protrusion To Mounting Surface:

0.830 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

0.750 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.875 inches

Bushing Hole Diameter:

0.875 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.437 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

90.0

Test Data Document:

81349-mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-prf-19207/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0

Mil-std (military Standard):

Mil-prf-19207 spec.