

View Online at <https://aerobasegroup.com/nsn/5920-01-511-1824>

Body Style:

Tube type

Terminal Material:

Brass or copper or copper alloy

Terminal Surface Treatment:

Silver plated

Overall Length:

Between 1.219 inches and 1.281 inches

Overall Diameter:

Between 0.246 inches and 0.254 inches

Case Material:

Ceramic or plastic

Continuous Current Rating In Amps:

25.000

Maximum Voltage Rating In Volts:

125.0 ac

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

End Application:

Panel, load interface; wsd: ohio class ssbn (trident)

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

10.0 200 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

10000.0

Precious Material:

Silver

Test Data Document:

81349-mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-15160/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01700

Mil-std (military Standard):

Mil-prf-15160 spec.