

View Online at <https://aerobasegroup.com/nsn/5920-01-512-4191>

**Body Material:**

Glass and plastic, mil-p-14, type mai-60

**Body Style:**

Bushing mounted type

**Overall Length:**

Between 2.775 inches and 2.785 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

Between 1.245 inches and 1.255 inches

**Panel Thickness:**

0.125 inches

**Environmental Protection:**

Watertight

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Brass

**Contact Surface Treatment:**

Brass

**Interruption Indicator Method:**

Incandescent lamp

**End Application:**

Mk5mod0, sequencer, launch; wsd: vertical launching system, mk-41

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

Between 1.075 inches and 1.085 inches

**Bushing Thread Length:**

0.892 inches

**Cap Diameter:**

Between 1.135 inches and 1.145 inches

**Bushing Hole Diameter:**

Between 0.876 inches and 0.886 inches

**Flatted Side Bushing Hole Length:**

Between 0.815 inches and 0.825 inches

**Screw Thread Diameter:**

0.138 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.000

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Terminal Type And Quantity:**

1 tab, solder lug and 1 threaded stud and 1 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0