

View Online at <https://aerobasegroup.com/nsn/5920-01-512-4191>

Body Material:

Glass and plastic, mil-p-14, type mai-60

Body Style:

Bushing mounted type

Overall Length:

Between 2.775 inches and 2.785 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 1.245 inches and 1.255 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Watertight

Mounting Hole Style:

Bushing mounting

Contact Material:

Brass

Contact Surface Treatment:

Brass

Interruption Indicator Method:

Incandescent lamp

End Application:

Mk5mod0, sequencer, launch; wsd: vertical launching system, mk-41

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

Between 1.075 inches and 1.085 inches

Bushing Thread Length:

0.892 inches

Cap Diameter:

Between 1.135 inches and 1.145 inches

Bushing Hole Diameter:

Between 0.876 inches and 0.886 inches

Flatted Side Bushing Hole Length:

Between 0.815 inches and 0.825 inches

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.000

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

1 tab, solder lug and 1 threaded stud and 1 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0