# NSN 5920-01-519-4750

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-519-4750

# Body Style:

Tube type

**Terminal Material:** 

Brass or copper or copper alloy

## **Terminal Surface Treatment:**

Nickel

#### **Overall Length:**

Between 1.219 inches and 1.281 inches

#### **Overall Diameter:**

Between 0.246 inches and 0.254 inches

#### Case Material:

Plastic, diallyl phthalate

**Continuous Current Rating In Amps:** 

6.000

#### Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

## **Circuit Over-current Interruption Type:**

Normal instantaneous

#### Interruption Indicator Method:

Opaque body

#### End Application:

Controller interface; wsd: ohio class ssbn (trident)

#### **Features Provided:**

Nonrenewable fusible element

#### Short-circuit/interrupt Current Rating In Amps:

100.0

#### Test Data Document:

81349-mil-prf-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349 - mil-prf-23419/9 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A01700

#### Mil-std (military Standard):

Mil-prf-23419 spec.