

View Online at <https://aerobasegroup.com/nsn/5920-01-528-9140>

**Body Style:**

Panel mounted type

**Overall Length:**

2.350 inches

**Overall Diameter:**

0.880 inches

**Panel Thickness:**

0.250 inches

**Environmental Protection:**

Shock proof and watertight

**Contact Material:**

Copper and copper alloy

**End Application:**

E/i 1051054g-4 (80249) los radio, an/vrc-99b, an/wld-1; wsd: an/wld- (v) remote mine hunting system

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

1.000 inches

**Current Carrying Rating In Amps:**

20.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Special Features:**

Mfg name: rf shielded/watertight panel mount type fuseholder for 3ag fuses; brass shielding cap finish: dull black; ambient temp: -40 to +85 degrees c

**Terminal Type And Quantity:**

1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0