

View Online at <https://aerobasegroup.com/nsn/5920-01-595-6243>

Body Style:

Bushing mounted type

Overall Length:

2.470 inches

Mounting Hole Quantity:

1

Overall Diameter:

1.260 inches

Panel Thickness:

0.060 inches

Environmental Protection:

Watertight

Mounting Hole Style:

Bushing mounting

Lens Color:

Amber

Contact Material:

Copper

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

680.0 kilohms

Indicating Lamp Voltage Range In Volts:

+34.0/+45.0

Length From Front Protrusion To Mounting Surface:

0.940 inches

Bushing Thread Length:

0.500 inches

Cap Diameter:

1.000 inches

Bushing Hole Diameter:

Between 0.877 inches and 0.882 inches

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-prf-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 threaded stud and 1 screw

Specification Data:

81349-mil-prf-19207/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0

Mil-std (military Standard):

Mil-prf-19207 spec.