## NSN 5920-01-615-7104

Receptacle Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-615-7104

View Online at https://aerobasegroup.com/nsn/5920-01-615-7104
Body Style:
Dual plug type
Overall Length:
1.18 inches
Overall Height:
0.938 inches
Overall Width:
1.81 inches
Mounting Hole Diameter:
0.156 inches
Mounting Hole Quantity:
2
Mounting Hole Style:
2 bushing mounting w/2 holes
Contact Material:
Brass
Fuse Accommodation Quantity:
2
Center To Center Distance Between Outside Mounting Holes Along Width:
0.974 inches
Bushing Hole Diameter:
0.875 inches
Center To Center Distance Between Bushing Holes:
0.800 inches
Center To Center Distance Between Keyway And Bushing Hole:
0.400 inches
Screw Thread Diameter:
8.0 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Internal Circuit Configuration And Pole Quantity:
2 pole, mainline, fused
Fuse Terminal Type Accommodated:
Ferrule w/threaded stud
Product Name:
Fuse, carrier
Voltage In Volts:
100.0
Special Features:
Panel thickness: 0.125 inches, indicating: incandescent lamp number 1764. Termina

Panel thickness: 0.125 inches, indicating: incandescent lamp number 1764. Terminals: threaded stud type, number 8-32unc-2a. Enclosure: dripproof.Temperature rise: f03a125v30a. Short circuit: f03a125v30a. Terminal strength: 20 pounds, salt spray corrosion: test condition b. Mechanical shock: method i

## NSN 5920-01-615-7104

Receptacle Fuseholder - Page 2 of 2



## Terminal Type And Quantity:

2 ferrule w/threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A014a0