

View Online at <https://aerobasegroup.com/nsn/5920-01-651-4992>

Body Material:

Plastic

Body Style:

Panel mounted type

Overall Length:

2.00 inches

Overall Height:

Between 2.070 inches and 2.110 inches

Overall Width:

Between 1.790 inches and 1.830 inches

Mounting Hole Diameter:

Between 0.147 inches and 0.157 inches

Mounting Hole Quantity:

2

Panel Thickness:

0.0187 inches

Environmental Protection:

Watertight

Mounting Hole Style:

Panel mounting w/2 or 3 holes

Lens Color:

Clear

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Incandescent lamp

End Application:

Power supply

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

330.0 ohms

Length From Front Protrusion To Mounting Surface:

1.060 inches

Cap Diameter:

Between 0.620 inches and 0.630 inches

Mounting Hole Height:

Between 1.578 inches and 1.610 inches

Mounting Hole Width:

Between 1.359 inches and 1.391 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.775 inches and 1.785 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.860 inches and 0.900 inches

Screw Thread Diameter:

0.640 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Product Name:

Fuseholder, extractor, post type blown fuse fh133w

Voltage In Volts:

33.0

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0