

View Online at <https://aerobasegroup.com/nsn/5920-01-651-4992>

**Body Material:**

Plastic

**Body Style:**

Panel mounted type

**Overall Length:**

2.00 inches

**Overall Height:**

Between 2.070 inches and 2.110 inches

**Overall Width:**

Between 1.790 inches and 1.830 inches

**Mounting Hole Diameter:**

Between 0.147 inches and 0.157 inches

**Mounting Hole Quantity:**

2

**Panel Thickness:**

0.0187 inches

**Environmental Protection:**

Watertight

**Mounting Hole Style:**

Panel mounting w/2 or 3 holes

**Lens Color:**

Clear

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Incandescent lamp

**End Application:**

Power supply

**Fuse Accommodation Quantity:**

2

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

330.0 ohms

**Length From Front Protrusion To Mounting Surface:**

1.060 inches

**Cap Diameter:**

Between 0.620 inches and 0.630 inches

**Mounting Hole Height:**

Between 1.578 inches and 1.610 inches

**Mounting Hole Width:**

Between 1.359 inches and 1.391 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 1.775 inches and 1.785 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 0.860 inches and 0.900 inches

**Screw Thread Diameter:**

0.640 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Product Name:**

Fuseholder, extractor, post type blown fuse fh133w

**Voltage In Volts:**

33.0

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0