

View Online at <https://aerobasegroup.com/nsn/5925-00-004-4024>

Body Style:

Multipole-multiple actuator type

Body Length:

3.719 inches

Body Width:

2.031 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.063 inches

Center To Center Distance Between Terminals Parallel To Width:

1.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.750 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.031 inches

Boss Height:

0.156 inches

Mounting Surface To Terminal End Distance:

3.429 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

208.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 200 pct all locations and 18.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

2.5 ac and 1.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 50.0 dc

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

1.200 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0