NSN 5925-00-005-3068

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-005-3068

Body Style:
Multipole-single actuator type
Body Length:
10.125 inches
Body Width:
4.125 inches
Body Height:
3.187 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
7.750 inches
Center To Center Distance Between Terminals Parallel To Width:
0.687 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
7.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.687 inches
Boss Height:
0.125 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
110.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
20000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
•
Trip Release Characteristic:
-

150.0 all locations

NSN 5925-00-005-3068 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
100.000 at 200 pct all locations and 300.000 at 200 pct all locations and 30.000 at 300 pct all locations and 80.000 at 300 pct all location
and 15.000 at 400 pct all locations and 45.000 at 400 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filig:
A030a0