## NSN 5925-00-005-3114

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-005-3114 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.125 inches **Body Height:** 3.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.062 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.187 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.125 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** 

**Trip Release Characteristic:** Time delay all locations

Magnetic all locations

## **NSN 5925-00-005-3114** Circuit Breaker - Page 2 of 2



| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
|--|
| 130.0 all locations  |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:                                  |
| Trip free  |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Internal Trip Release Configuration:                                   |
| Series trip all locations  |
| Trip Delay Time In Seconds Per Rated Continuous Current:               |
| 200.000 at 200 pct all locations                                       |
| Inclosure Protection Type For Which Designed:                          |
| Fungus resistant and moisture resistant                                |
| Frequency In Hertz:  |
| 60.0 all locations   |
| Terminal Type And Quantity:  |
| 6 compression  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |
|  |