## NSN 5925-00-008-4375

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-008-4375 **Body Style:** Multipole-single actuator type **Body Length:** 3.344 inches **Body Width:** 3.000 inches **Body Height:** 2.312 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 terminal **Maximum Continuous Load Current Rating Per Pole:** 25.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

At pole two

**Actuator Position Designation:** 

## NSN 5925-00-008-4375

Circuit Breaker - Page 2 of 2



## **Trip Delay Time In Seconds Per Rated Continuous Current:**

42.000 at 200 pct all locations and 180.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:** 

Fungus resistant

**Trip Release Ambient Tempurature Rating:** 

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

3 clip and 3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A030a0