

View Online at <https://aerobasegroup.com/nsn/5925-00-008-4398>

Thread Pitch Diameters:

+0.3503 to 0.3537 inches

Body Style:

Single pole type

Bushing Length:

0.380 inches

Body Length:

1.500 inches

Body Width:

0.625 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.844 inches and 0.906 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac single location and 500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct single location and 5.500 at 200 pct single location

Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Special Features:

Inertial delay included on item

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0