

View Online at <https://aerobasegroup.com/nsn/5925-00-009-3280>

**Body Style:**

Single pole type

**Overall Length:**

3.625 inches

**Body Width:**

1.375 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.125 inches

**Mounting Surface To Terminal End Distance:**

2.328 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

7.0 amperes ac single location and 7.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location and 1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct single location and 100.000 at 200 pct single location

**Inclsure Protection Type For Which Designed:**

Moisture resistant

**Trip Release Ambient Tempurature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0