

View Online at <https://aerobasegroup.com/nsn/5925-00-011-2540>

Body Style:

Multipole-multiple actuator type

Body Length:

3.220 inches

Body Width:

1.480 inches

Body Height:

2.580 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.225 inches

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Cubic Measure:

12.295 cubic inches

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Trip Delay Time In Seconds Per Rated Continuous Current:

120.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 screw and 2 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0