# NSN 5925-00-012-9365

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-012-9365

# Body Style:

Single pole type

# **Bushing Length:**

Between 0.219 inches and 0.281 inches

# Body Length:

Between 0.719 inches and 0.781 inches

## Body Width:

Between 0.531 inches and 0.593 inches

### **Case Material:**

Plastic

# Center To Center Distance Between Terminals Parallel To Length:

Between 0.672 inches and 0.734 inches

**Fragility Factor:** 

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.919 inches and 1.981 inches

# Pole Quantity:

1

Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

### Storage Type:

General purpose warehouse

# Thready Qty Per Inch (tpi):

32

# Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location and 3.0 amperes dc single location

### **Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac single location and 28.0 dc single location

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

### **Circuit Protection Type:**

Overcurrent single location

### Trip Release Method:

Thermal single location

### **Trip Release Characteristic:**

Time delay single location

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

#### **Reset Method:**

Manual

# NSN 5925-00-012-9365

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location and 20.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Vibrationproof and fungus resistant and moisture resistant **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location **Frequency In Hertz:** 400.0 single location **Unpackaged Unit Weight:** 38.0 grams **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0