NSN 5925-00-016-3758

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-016-3758

Body Style:

Multipole-multiple actuator type

Body Length:

2.530 inches

Body Width:

2.280 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

2.500 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

700.0 milliamperes dc first location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 dc first location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay third location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-016-3758 Circuit Breaker - Page 2 of 2

Reset Method:	
Manual	
Main Contact Tripping Mechanism Type:	
Trip free	
Manual Actuator Type And Quantity:	
3 toggle	
Actuator Function:	
Trip-reset	
Actuator Position Designation:	
At each pole	
External Actuator Linkage Arrangement:	
One, two, and three linked	
Internal Trip Release Configuration:	
Series trip all locations	
Thread Size:	
0.138 inches	
Trip Delay Time In Seconds Per Rated Continuous Current:	
0.600 at 200 pct third location	
Inclosure Protection Type For Which Designed:	
Fungus resistant	
Frequency In Hertz:	
60.0 third location	
Thread Series Designator:	
Unc	
Terminal Type And Quantity:	
6 threaded stud	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	

