

View Online at <https://aerobasegroup.com/nsn/5925-00-018-9198>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.250 inches and 0.312 inches

Body Length:

Between 1.187 inches and 1.249 inches

Body Width:

2.000 inches

Body Height:

3.105 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Center To Center Distance Between Terminals Parallel To Width:

0.500 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

Thd bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct all locations and 20.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shockproof and vibrationproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

0.375 pounds

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0