Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-021-6970

Thread Pitch Diameters:
+0.3503 to 0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
Between 0.360 inches and 0.380 inches
Body Length:
Between 1.464 inches and 1.526 inches
Body Width:
Between 1.841 inches and 1.906 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
Between 0.870 inches and 0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.620 inches and 0.630 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
Between 1.647 inches and 1.709 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac first location
Operating Voltage Type And Rating Per Pole In Volts:
50.0 dc second location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
500.0 dc second location
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 3.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Frequency In Hertz:

400.0 first location

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0