NSN 5925-00-026-1977

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-026-1977

#### **Body Style:**

Multipole-multiple actuator type

### **Bushing Length:**

0.130 inches

# Body Length:

2.000 inches

## Body Width:

1.500 inches

#### **Case Material:**

Plastic

### Center To Center Distance Between Terminals Parallel To Length:

#### 1.560 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

## Mounting Surface To Terminal End Distance:

2.032 inches

# **Pole Quantity:**

2

## Mounting Facility Type And Quantity:

4 threaded hole

### Thready Qty Per Inch (tpi):

32

### Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

### **Trip Release Characteristic:**

Time delay all locations

### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

### Main Contact Tripping Mechanism Type:

Trip free

# NSN 5925-00-026-1977

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

# Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 all locations

# Test Data Document:

81349-milc55629-9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:

Unc Terminal Type And Quantity: 4 screw Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A030a0