# NSN 5925-00-026-4781

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-026-4781

| Body Style:  |
|--|
| Single pole type   |
| Overall Length:  |
| 2.000 inches   |
| Body Width:  |
| 1.250 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 0.641 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.250 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.574 inches   |
| Mounting Surface To Terminal End Distance:                                   |
| 1.266 inches   |
| Pole Quantity:   |
| 1  |
| Mounting Facility Type And Quantity:   |
| 2 unthreaded hole  |
| Storage Type:  |
| General purpose warehouse  |
| Maximum Continuous Load Current Rating Per Pole:                             |
| 15.0 amperes ac single location and 15.0 amperes dc single location          |
| Operating Voltage Type And Rating Per Pole In Volts:                         |
| 110.0 ac single location and 30.0 dc single location                         |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:      |
| 600.0 ac single location and 600.0 dc single location                        |
| Circuit Protection Type:   |
| Overcurrent single location  |
| Trip Release Method:   |
| Thermal single location  |
| Trip Release Characteristic:   |
| Time delay single location   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:       |
| 130.0 single location  |
| Reset Method:  |
| Automatic  |
| Internal Trip Release Configuration:   |
| Series trip single location  |
| Trip Delay Time In Seconds Per Rated Continuous Current:                     |
| 6.000 at 200 pct single location and 45.000 at 200 pct single location       |
|  |

# NSN 5925-00-026-4781

Circuit Breaker - Page 2 of 2



### Inclosure Protection Type For Which Designed:

Fungus resistant

### Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

## Frequency In Hertz:

60.0 single location

# Unpackaged Unit Weight:

1.500 ounces

# Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A030a0