

View Online at <https://aerobasegroup.com/nsn/5925-00-033-7885>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.490 inches

**Body Length:**

1.760 inches

**Body Width:**

2.000 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Width:**

1.376 inches

**Mounting Surface To Terminal End Distance:**

0.450 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

3 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 800 pct pascal all locations and 0.800 18 stage pascal all locations

**Inclosure Protection Type For Which Designed:**

Moisture resistant and hermetically sealed

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0