

View Online at <https://aerobasegroup.com/nsn/5925-00-033-7885>

Body Style:

Multipole-single actuator type

Bushing Length:

0.490 inches

Body Length:

1.760 inches

Body Width:

2.000 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Width:

1.376 inches

Mounting Surface To Terminal End Distance:

0.450 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 800 pct pascal all locations and 0.800 18 stage pascal all locations

Inclosure Protection Type For Which Designed:

Moisture resistant and hermetically sealed

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0