

View Online at <https://aerobasegroup.com/nsn/5925-00-041-1935>

Body Style:

Single pole type

Bushing Length:

0.390 inches

Body Length:

1.140 inches

Body Width:

0.570 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.890 inches

Mounting Surface To Terminal End Distance:

2.260 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

28

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 400 pct single location and 9.000 at 400 pct single location

Trip Release Ambient Temperature Rating:

70.0 degrees fahrenheit single location

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Un

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0